ADVANCED DURABILITY FOR LONGER LASTING BEAUTY**









Product Guide & Specifications



ENGINEERED TO IMPRESS Durability 03 Workability 05 Sustainability 07 Beauty 09 **PRODUCTS** Lap Siding 13 Shakes & Shingles 15 Panel & Vertical Siding 17 Trim & Fascia 19 Soffit 21 **APPLICATIONS** New Home 25 Remodel 26 **Outdoor Building Solutions** 27 **Light Commercial** 28 **INSPIRATION** Product Usage Photography 31 **SPECIFICATIONS** 39 Cedar Texture Lap Smooth Finish Lap (Strand) 40 Colonial Beaded Lap 41 12" & 16" Bold Profile Lap 42 Smooth Finish Lap (Fiber) 43 Lap Siding Coverage Chart 44 Perfection Shingle 45 Cedar Texture Shakes 46 Cedar Texture Panel 47 Stucco Texture Panel 49 Smooth Finish Panel (Fiber) 50 Reverse Board & Batten 51 Vertical Siding 52 Cedar Texture Trim 53 Reversible Trim (Fiber) 54 Smooth Finish Trim (Strand) 55 Cedar Texture Soffit 56

Vented Soffit

Smooth Finish Soffit (Fiber)

57

58





A NATURAL DEFENSE AGAINST NATURE

All LP® SmartSide® products are treated to the core through our proprietary SmartGuard® process. With four components of protection, the SmartGuard process adds strength and helps LP SmartSide products withstand impacts, freeze/thaw cycles, high humidity, fungal decay and more.

See more about how LP SmartSide products are made at YouTube.com/LPSmartSide.



FOUR COMPONENTS OF PROTECTION

LP's proprietary SmartGuard® manufacturing process ensures that every LP SmartSide Trim & Siding product is treated with an advanced formula of adhesive resins, water-resistant waxes and zinc borate, after which a waterresistant, resin-saturated overlay is bonded to the product. The result: four components of protection against water damage, termites and fungal decay.











OUTSTANDING IMPACT RESISTANCE

Testing shows that LP SmartSide strand products resist impact better than vinyl and fiber cement siding, which means they can stand up better against everything from everyday bumps to airborne storm debris. And because it doesn't break as easily as fiber cement siding, LP SmartSide strand siding is also easier to handle and install, and results in less waste.

HAIL AND WIND RESISTANCE

Third-party test results demonstrate that LP SmartSide lap siding resisted hail damage better than fiber cement and vinyl. In fact, the LP SmartSide warranty covers impacts from hail up to 1.75" in diameter. LP SmartSide lap siding is also designed to withstand tough storms with wind gusts of up to 200 miles per hour. Refer to ESR-1301, Table 2B, Lap Siding.

RESISTANCE TO FUNGAL DECAY AND TERMITES

Since 1996, LP SmartSide strand substrate siding has undergone brutal testing in Hilo, Hawaii. An average temperature of more than 70 degrees, high levels of humidity, and almost 170 inches of annual rainfall make Hilo's climate the perfect breeding ground for termites, moisture and fungal decay. Yet our Exterior Exposure Program continues to validate that LP SmartSide siding performs over time.



A STRONG WARRANTY BEHIND IT

LP has your back with an industry-leading, transferable limited warranty: a 50-year prorated limited warranty with a 5-year 100% labor and material replacement warranty.

*For complete warranty details visit LPCorp.com

WORKS THE WAY WOOD IS SUPPOSED TO

LP® SmartSide® treated engineered wood siding cuts out the time you spend dealing with warped and split pieces when properly stored and applied. Virtually every piece leaves the mill straight and ready to use. Plus, you'll get lengths up to 16´, which may mean fewer seams and less waste to haul off the site.

MAKES BUILDING EASIER, FASTER, MORE EFFICIENT

LP SmartSide Trim & Siding cuts with standard woodworking tools, unlike fiber cement cladding that recommends expensive diamond blades. LP SmartSide products weigh less, resist breakage during handling, and make installation more efficient. Plus, all LP SmartSide products come pre-primed and ready to paint to help you save time.

LP HAS WORKABILITY NAILED

- Works and cuts like traditional wood
- Requires fewer tools
- Weighs less, easier to carry, less breakage than fiber cement
- Longer lengths may mean fewer seams and less waste

Watch our Building Science videos to see how LP makes treated engineered wood products last longer at YouTube.com/LPSmartSide.







We're not just building for the future; we're helping to protect it by using Sustainable Forestry Initiative® (SFI) certified forest management and fiber sourcing systems to help ensure that our wood comes from well-managed forests.

NATURALLY SUSTAINABLE

The LP SmartSide manufacturing process begins with wood, a renewable resource, grown and gathered under strict SFI standards. We target fast-growing trees and use 99% of the log for either the product or the fuel to make it. Plus, all binding agents and resins are low-emitting.

RESPONSIBLY MADE WITH WOOD

- Responsibly made with a renewable resource—wood
- 99% of the log is used
- Qualifies for green building programs

Learn more about LP's environmental programs at LPCorp.com.





BEAUTY IN EVERY STYLE

Siding texture plays a big role in a home's curb appeal. That's why LP® SmartSide® Trim & Siding is available in traditional cedar and smooth finishes that are both built with engineered wood strand technology. So whether you're building a traditional craftsman or a modern masterpiece, you'll be able to deliver the same advanced durability and longer lasting beauty.







SMOOTH FINISH LAP

GREATE SOUR OWN GUSTOM Choose your style. Choose your colors. Get the look you want. That's the beauty of working with treated engineered wood. LP® SmartSide® products offer you the versatility to achieve stunning results with ease. **PICTURE IT BEAUTIFUL** LP SmartSide products offer homeowners the bold look of their signature cedar-grain texture in profiles that are always in style. It's been the siding of choice for 20 years for homeowners who want uncompromising quality and distinctive curb appeal. Featured: LP SmartSide Lap, Cedar Texture Shakes (Staggered), Trim & Fascia





TRADITIONAL, BOLD, SUBTLE, DARING, MODERN

Create the look you want with a versatile selection of LP® SmartSide® products. Engineered to stand up to extreme weather, LP SmartSide Lap Siding is a natural, durable choice for structures in any region. Plus, it's the perfect companion cladding for structures partially finished in stucco, stone and brick.



CEDAR TEXTURE LAP



COLONIAL BEADED LAP



NEW SMOOTH FINISH STRAND LAP



12" BOLD PROFILES



16" BOLD PROFILES



SMOOTH FINISH FIBER LAP



ATTENTION TO DETAIL

When you use LP® SmartSide® Shakes & Shingles on your projects, people will notice your attention to every detail. The beautiful aesthetic can be used for accents, gables or siding walls and will take curb appeal to the next level. It's a must-have product for when you want your craftsmanship to stand out on any home, shed or light commercial building.



CEDAR TEXTURE SHAKES



PERFECTION SHINGLE



PANEL THAT PERFORMS

Tough to the core, LP® SmartSide® Panel Siding is a treated engineered wood product that's more durable, stable and consistent than traditional wood panels. It's easy to recommend for light commercial, shed and residential applications that require a premium look and the toughness to combat extreme weather.



CEDAR TEXTURE PANEL



REVERSE BOARD & BATTEN



STUCCO TEXTURE PANEL



SMOOTH FINISH PANEL

STRONG, STYLISH VERTICAL SIDING

LP SmartSide Vertical Siding lets you re-create the charming appearance of board and batten while providing the added protection of the SmartGuard® process.



VERTICAL SIDING



OUTLINE YOUR VISION

LP® SmartSide® Trim & Fascia are the finishing touch that's the first to get noticed. With its smooth finish or deep cedar-grain texture and variety of widths and thicknesses, you can add custom design accents that take curb appeal to the next level. LP SmartSide Trim is a must-have product for when you want your craftsmanship to stand out on any home, shed or light commercial building.



CEDAR TEXTURE TRIM



REVERSIBLE TRIM



NEW SMOOTH FINISH STRAND TRIM



AN INNOVATIVE ALTERNATIVE TO MDO, PLYWOOD, VINYL OR METAL VENTS

When you use LP® SmartSide® Soffit on your projects, people will notice your attention to every detail. You'll get the same wood grain or smooth look that matches other LP SmartSide products in a soffit that's pre-cut to the width you need. Vented soffits are also available with precisely cut, bug-resistant vents.



CEDAR TEXTURE SOFFIT



SMOOTH FINISH SOFFIT



VENTED SOFFIT



LP® SmartSide® Trim & Siding products come in a variety of styles, including smooth finish and cedar-grain textures, to help you create exactly the look you want. Use them on their own or to complement other claddings, such as brick or stone. They're beautiful on homes and in other applications. With products this versatile, the possibilities are virtually endless.





NEW HOME

Every homeowner wants a custom look that they can take pride in. They want a style that helps differentiate their new home from the one next door. LP® SmartSide® products give builders and architects the ability to design a signature look with a wow-factor that leaves a lasting impression.

LPSmartSide.com/Applications/NewHome

POPULAR CHOICES FOR NEW HOMES:

- LP SmartSide Lap Siding
- LP SmartSide Cedar Texture Shakes
- LP SmartSide Trim & Fascia
- LP SmartSide Soffit
- LP SmartSide Perfection Shingle
- LP SmartSide Vertical Siding



REMODEL

LP® SmartSide® products can help give any home a new life with their beautiful selection of styles and profiles. They easily transform homes from boring to bold with their rich cedargrain texture. When you start using LP SmartSide products, it's easy to see why homeowners love them and professional remodelers love to work with them.

LPSmartSide.com/Applications/Remodel

POPULAR CHOICES FOR REMODELING:

- LP SmartSide Lap Siding
- LP SmartSide Cedar Texture Shakes
- LP SmartSide Trim & Fascia
- LP SmartSide Soffit



OUTDOOR BUILDING SOLUTIONS®

LP® Outdoor Building Solutions® engineered wood products feature innovations that help offer more value to customers. With innovations like SilverTech® panel for a brighter and cooler interior and SmartFinish® overlay for a tough, attractive appearance, LP Outdoor Building Solutions products give you quality you can see inside and out.

LPShed.com

POPULAR CHOICES FOR OUTDOOR BUILDINGS:

- LP® SmartSide® Panel Siding
- LP SmartSide Panel Siding with SilverTech
- LP SmartSide Panel Siding with SmartFinish
- LP SmartSide Lap Siding
- LP ProStruct® Flooring with SmartFinish
- LP ProStruct Roof with SilverTech
- LP SmartSide Trim & Fascia





LIGHT COMMERCIAL

Light commercial buildings put any exterior cladding to the test, but few can withstand the increased demands and come out looking as beautiful as LP® SmartSide® products. LP SmartSide Panel and Lap Siding are fast becoming a popular choice for building owners who want the extraordinary curb appeal of wood-grain texture. It's a welcome alternative to metal cladding that's making the light commercial landscape more beautiful every day.

LPSmartSide.com/Applications/LightCommercial

POPULAR CHOICES FOR LIGHT COMMERCIAL:

- LP SmartSide Panel Siding
- LP SmartSide Lap Siding
- LP SmartSide Trim & Fascia
- LP SmartSide Soffit

INSPIRING POSSIBILITIES.

OPTIONS TO REALIZE ANY VISION

LP® SmartSide® products come in a variety of styles, including smooth finish and cedar-grain textures, to help you create exactly the look you want. Use them on their own or to complement other claddings, such as brick or stone. They're beautiful on homes and in other applications. With products this versatile, the possibilities are virtually endless.













TAKEA CLOSER LOOK

GET THE DETAILS ON EACH PRODUCT

LP® SmartSide® products come in different lengths, widths, textures, profiles and substrates, so there's an ideal product for virtually any set of needs. Each option has its own unique combination of advantages. Find all those details and product specifications here.

CEDAR TEXTURE LAP

THE BOLD LOOK OF CEDAR WITHOUT MANY OF THE WORRIES

- One of the most durable lap siding options in the market today
- 16' length can result in faster installation
- May create fewer seams than traditional 12' siding
- Pre-primed for exceptional paint adhesion
- Self-aligning SmartLock™ option eliminates the need to measure and set lap reveal; eliminating this step in the process is likely to speed up the installation process
- APA-certified lap siding
- Treated engineered wood strand substrate





Cedar Texture

ALSO AVAILABLE IN FIBER SUBSTRATE

- CPA-certified lap siding
- Treated engineered wood fiber substrate








76 SERIES CEDAR TEXTURE LAP (STRAND)





76 SERIES SMARTLOCK CEDAR

DESCRIPTION	LENGTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
38 Series Cedar Texture Lap (strand)	16 ft. (192 in.)(4.9 m)	5.84 in. (14.8 cm)	0.315 in. (8 mm)	25796	1.5 PSF
	16 ft. (192 in.)(4.9 m)	6.84 in. (17.4 cm)	0.315 in. (8 mm)	40610	1.5 PSF
	16 ft. (192 in.)(4.9 m)	7.84 in. (19.9 cm)	0.315 in. (8 mm)	25797	1.5 PSF
	16 ft. (192 in.)(4.9 m)	11.84 in. (30.1 cm)	0.315 in. (8 mm)	25799	1.5 PSF
76 Series Cedar Texture Lap (strand)	16 ft. (192 in.)(4.9 m)	5.84 in. (14.8 cm)	0.375 in. (10 mm)	25785	1.5 PSF
	16 ft. (192 in.)(4.9 m)	7.84 in. (19.9 cm)	0.375 in. (10 mm)	25786	1.5 PSF
	16 ft. (192 in.)(4.9 m)	11.84 in. (30.1 cm)	0.375 in. (10 mm)	25787	1.5 PSF
76 Series Cedar Texture Lap (fiber)	16 ft. (192 in.)(4.9 m)	5.84 in. (14.8 cm)	0.375 in. (10 mm)	25922	2 PSF
	16 ft. (192 in.)(4.9 m)	7.84 in. (19.9 cm)	0.375 in. (10 mm)	25923	2 PSF
	16 ft. (192 in.)(4.9 m)	9.47 in. (24.1 cm)	0.375 in. (10 mm)	25924	2 PSF
	16 ft. (192 in.)(4.9 m)	11.84 in. (30.1 cm)	0.375 in. (10 mm)	25925	2 PSF
76 Series SmartLock Cedar Texture Lap (strand)	16 ft. (192 in.)(4.9 m)	7.84 in. (19.9 cm)	0.375 in. (10 mm)	30317	1.5 PSF
120 Series Self-Aligning Cedar Texture Lap (fiber)	16 ft. (192 in.)(4.9 m)	7.92 in. (20.1 cm)	0.450 in. (11 mm)	25905	2 PSF

SMOOTH FINISH LAP (STRAND)

SMOOTH APPEARANCE, ADVANCED DURABILITY OF ENGINEERED WOOD

- Advanced Durability for Longer Lasting BeautyTM
- Holds up in extreme weather including moisture, hail, freeze/thaw cycles, and up to 200 mph wind gusts
- Treated with the SmartGuard® process for superior protection against the weather, fungal decay and termites
- 16' length can result in faster installation and fewer seams
- Pre-primed for exceptional paint adhesion
- Backed by an industry-leading 5/50-year limited warranty
- Treated engineered wood strand substrate





Smooth Finish

38 SERIES SMOOTH FINISH LAP (STRAND)



DESCRIPTION	LENGTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
38 Series Smooth Finish Lap (strand)	16 ft. (192 in.)(4.9 m)	5.84 in. (14.8 cm)	0.315 in. (8 mm)	41338	1.5 PSF
	16 ft. (192 in.)(4.9 m)	7.84 in. (19.9 cm)	0.315 in. (8 mm)	41339	1.5 PSF
	16 ft. (192 in.)(4.9 m)	11.84 in. (30.1 cm)	0.315 in. (8 mm)	41340	1.5 PSF

COLONIAL BEADED LAP


CUTTING EDGE MEETS CLASSICAL

- Colonial Beaded Lap siding endows homes with authentic American style
- Drip lines cast crisp shadows for maximum curb appeal
- Pre-primed for exceptional paint adhesion
- 16' length can result in faster installation and fewer seams
- Treated engineered wood fiber substrate

Sequoia Texture

Smooth Finish

COLONIAL BEADED SEQUOIA TEXTURE LAP (FIBER)



COLONIAL BEADED SMOOTH FINISH LAP (FIBER)



DESCRIPTION	LENGTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
Colonial Beaded Sequoia Texture Lap (fiber)	16 ft. (192 in.)(4.9 m)	7.94 in. (20.2 cm)	0.375 in. (10 mm)	25904	2 PSF
Colonial Beaded Smooth Finish Lap (fiber)	16 ft. (192 in.)(4.9 m)	7.94 in. (20.2 cm)	0.375 in. (10 mm)	25903	2 PSF
	16 ft. (192 in.)(4.9 m)	8.94 in. (22.7 cm)	0.375 in. (10 mm)	25909	2 PSF

12" AND 16" BOLD PROFILE LAP

GENUINE DETAIL

- Distinctive Triple 4" and Double 5" profiles
- Shiplap edges make it easier to level and apply
- Pre-primed for exceptional paint adhesion
- 16' length can result in faster installation and fewer seams

_11.86 in (30.1 cm)-

- The extra-wide 16" siding comes in three profiles: Quad 4", Triple 5" and Double 8"
- Treated engineered wood fiber substrate

TRIPLE 4" BOLD PROFILE CEDAR TEXTURE LAP (FIBER)



12" Bold Profile




16" Bold Profile

0.450 in. (11 mm)




DOUBLE 5" BOLD PROFILE CEDAR TEXTURE LAP (FIBER)






Cedar Texture


QUAD 4" BOLD PROFILE CEDAR TEXTURE LAP (FIBER)



TRIPLE 5" BOLD PROFILE CEDAR TEXTURE LAP (FIBER)



DOUBLE 8" BOLD PROFILE CEDAR TEXTURE LAP (FIBER)



DESCRIPTION	LENGTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
Triple 4" Bold Profile Cedar Texture Lap (fiber)	16 ft. (192 in.)(4.9 m)	11.86 in. (30.1 cm)	0.450 in. (11 mm)	25906	2 PSF
Double 5" Bold Profile Cedar Texture Lap (fiber)	16 ft. (192 in.)(4.9 m)	11.86 in. (30.1 cm)	0.450 in. (11 mm)	25907	2 PSF
Quad 4" Bold Profile Cedar Texture Lap (fiber)	16 ft. (192 in.)(4.9 m)	15.94 in. (40.5 cm)	0.450 in. (11 mm)	25908	2 PSF
Triple 5" Bold Profile Cedar Texture Lap (fiber)	16 ft. (192 in.)(4.9 m)	15.94 in. (40.5 cm)	0.450 in. (11 mm)	25910	2 PSF
Double 8" Bold Profile Cedar Texture Lap (fiber)	16 ft. (192 in.)(4.9 m)	15.94 in. (40.5 cm)	0.450 in. (11 mm)	25911	2 PSF

SMOOTH FINISH LAP (FIBER)

A TRADITIONAL, SUBTLE LOOK

- Traditional look that accentuates the architectural features of any home
- Smooth finish for a clean appearance
- Pre-primed for exceptional paint adhesion
- 16' length can result in faster installation and fewer seams
- Treated engineered wood fiber substrate





25920

25921

2 PSF

2 PSF


Smooth finish

0.375 in. (10 mm)

0.375 in. (10 mm)

76 SERIES SMOOTH FINISH LAP (FIBER)

5.84 in., 7.84 in. or 11.84 in. (14.8 cm, 19.9 cm or 30.1 cm)



7.84 in. (19.9 cm)

11.84 in. (30.1 cm)

16 ft. (192 in.)(4.9 m)

16 ft. (192 in.)(4.9 m)

5000

342 pcs.

251 pcs.

5000

1667 pcs.

Lap Sidir	ng			F	Reveal (size)				
Area (sq.	ft.)	3-7/8" (5")	4-7/8" (6")	5 -7/8" (7")	6 -7/8" (8'	()	8 1/2" (9-1/2")	10	-7/8″ (12″)
100		20 pcs.	16 pcs.	13 pcs.	11 pcs.		9 pcs.		7 pcs.
200		39 pcs.	31 pcs.	26 pcs.	22 pcs.		18 pcs.		14 pcs.
300		59 pcs.	47 pcs.	39 pcs.	33 pcs.		27 pcs.		21 pcs.
400		78 pcs.	62 pcs.	52 pcs.	44 pcs.		35 pcs.		28 pcs.
500		97 pcs.	77 pcs.	64 pcs.	55 pcs.		44 pcs.		35 pcs.
600		117 pcs.	93 pcs.	77 pcs.	66 pcs.		53 pcs.		42 pcs.
700		136 pcs.	108 pcs.	90 pcs.	77 pcs.		62 pcs.		49 pcs.
800		155 pcs.	124 pcs.	103 pcs.	88 pcs.		71 pcs.		56 pcs.
900		175 pcs.	139 pcs.	115 pcs.	99 pcs.		79 pcs.		63 pcs.
1000		194 pcs.	154 pcs.	128 pcs.	110 pcs.		88 pcs.		69 pcs.
1500		291 pcs.	231 pcs.	192 pcs.	164 pcs.		132 pcs.	1	04 pcs.
2000		388 pcs.	308 pcs.	256 pcs.	219 pcs.		177 pcs.		138 pcs.
2500		484 pcs.	385 pcs.	320 pcs.	273 pcs.		221 pcs.		173 pcs.
3000		581 pcs.	462 pcs.	383 pcs.	328 pcs.		265 pcs.	2	207 pcs.
3500		678 pcs.	539 pcs.	447 pcs.	382 pcs.		309 pcs.	2	242 pcs.
4000		755 pcs.	616 pcs.	511 pcs.	437 pcs.		353 pcs.	:	276 pcs.
4500		871 pcs.	693 pcs.	575 pcs.	491 pcs.		397 pcs.		311 pcs.
5000		968 pcs.	770 pcs.	639 pcs.	546 pcs.		441 pcs.	3	345 pcs.
old Profiles	Revea	al (size)	Cedar Texture	Reveal ((size)	Perfection		Reveal (size	s)
Area (sq. ft.)	11″ (12″)	15″ (16″)	Shakes Area (sq. ft.)	9″ (12″)	10″ (12″)	Shingle Area (sq. ft.)	5-1/2" (8")	6" (8")	6-1/2″ (8
100	7 pcs.	6 pcs.	100	34 pcs.	30 pcs.	100	55 pcs.	51 pcs.	47 pcs
200	14 pcs.	11 pcs.	200	67 pcs.	60 pcs.	200	110 pcs.	101 pcs.	93 pc:
300	21 pcs.	16 pcs.	300	100 pcs.	90 pcs.	300	165 pcs.	151 pcs.	139 pc
				·	·		219 pcs.		
400 500	28 pcs.	21 pcs.	400 500	134 pcs.	120 pcs.	400 500	•	201 pcs. 251 pcs.	186 pc
600	35 pcs. 42 pcs.	26 pcs. 31 pcs.	600	167 pcs.	150 pcs.	600	274 pcs. 329 pcs.	301 pcs.	232 pc
700	42 pcs. 48 pcs.	36 pcs.	700	234 pcs.	210 pcs.	700	383 pcs.	351 pcs.	324 pc
800	55 pcs.	41 pcs.	800	267 pcs.	240 pcs.	800	438 pcs.	402 pcs.	371 pc
900	62 pcs.	46 pcs.	900	300 pcs.	270 pcs.	900	493 pcs.	452 pcs.	417 pc
1000			1000			1000		·	
1500	69 pcs.	51 pcs. 76 pcs.	1500	334 pcs. 500 pcs.	300 pcs. 450 pcs.	1500	547 pcs. 821 pcs.	502 pcs. 752 pcs.	463 pc
2000			2000	667 pcs.	600 pcs.	2000	1094 pcs.	1003 pcs.	926 pc
2500	137 pcs.	101 pcs.	2500			2500			
2000	171 pcs.	126 pcs.	2500	834 pcs.	750 pcs.	2500	1368 pcs.	1254 pcs.	1157 pc
3000	206 255	151 000	2000	1000 200	900 200	2000	16/11	1504	1200
3000	206 pcs.	151 pcs.	3000	1000 pcs.	900 pcs.	3000	1641 pcs.	1504 pcs.	
3500	240 pcs.	176 pcs.	3500	1167 pcs.	1050 pcs.	3500	1915 pcs.	1755 pcs.	1620 pc
									1389 pc 1620 pc 1851 pc 2083 pc

2735 pcs.

2507 pcs.


1500 pcs.

Specifications: LP® SmartSide® Shakes & Shingles

PERFECTION SHINGLE

A TRADITIONAL, SUBTLE LOOK

- Features fine sawn wood texture with no knots
- Balance of cedar like texture and the clean lines of shingles with a 5.5" to 6.5" reveal
- Beautiful aesthetic for accents, gables or siding walls
- Pre-primed for exceptional paint adhesion
- Perfect for a wide range of applications





DESCRIPTION	LENGTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
Perfection Shingle Lap (fiber)	4 ft. (48.63 in.)(1.2 m)	7.88 in. (200.2 mm)	0.375 in. (10 mm)	40796	1.5 PSF

Specifications: LP® SmartSide® Shakes & Shingles

CEDAR TEXTURE SHAKES

THE LUXURIOUS APPEAL OF CEDAR

- The look of traditional cedar with easier maintenance over time
- Staggered edges offer a lively, textured effect
- Can be used on all exterior walls or as a decorative accent
- Shiplap ends for seamless appearance
- Reversible staggered or straight edge offers exceptional design versatility
- Treated engineered wood fiber substrate




Cedar Texture


Staggered



Straight

CEDAR TEXTURE SHAKES (FIBER)





DESCRIPTION	LENGTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
Cedar Texture Shakes (fiber)	4ft. (48.56 in.)(1.2 m)	11.69 in. (29.7 cm)	0.375 in. (10 mm)	28541	2 PSF

CEDAR TEXTURE PANEL

RATED FOR STRUCTURAL USE BY APA®

- Shiplap edges with advanced bead system for easier alignment
- Pre-primed for exceptional paint adhesion
- Significantly lighter than comparable fiber cement panel
- Strong enough to be nailed directly to stud, making additional sheathing unnecessary in many applications
- Eliminates need for additional bracing on load-bearing walls
- Ideal exterior for homes in areas of high winds or seismic activity
- Treated engineered wood strand substrate


ALSO AVAILABLE IN FIBER SUBSTRATE

- Not rated for structural use
- Treated engineered wood fiber substrate


GROOVE DETAIL




38 SERIES CEDAR TEXTURE PANEL 8" O.C. (STRAND)




76 SERIES CEDAR TEXTURE PANEL 4" & 8" O.C. (STRAND)



190 SERIES CEDAR TEXTURE PANEL 8" O.C. (STRAND)




76 SERIES CEDAR TEXTURE SIDING PANEL AND SOFFIT 8" O.C. (FIBER)






Cedar Texture


38 SERIES CEDAR TEXTURE PANEL - NO GROOVE (STRAND)




76 SERIES CEDAR TEXTURE PANEL - NO GROOVE (STRAND)



190 SERIES CEDAR TEXTURE PANEL - NO GROOVE (STRAND)



76 SERIES CEDAR TEXTURE SIDING PANEL AND SOFFIT – SQUARE EDGE (FIBER)



DESCRIPTION	LENGTH	GROOVE	GROOVE WIDTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
38 Series Cedar Texture Panel 8" o.c. (strand)	6 ft. (72 in.)(1.8 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.315 in. (8 mm)	27805	1.5 PSF
	7 ft. (84 in.)(2.1 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.315 in. (8 mm)	27806	1.5 PSF
	8 ft. (96 in.)(2.4 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.315 in. (8 mm)	25840	1.5 PSF
	9 ft. (108 in.)(2.7 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.315 in. (8 mm)	25843	1.5 PSF
	10 ft. (120 in.)(3.0 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.315 in. (8 mm)	25844	1.5 PSF
	12 ft. (144 in.)(3.7 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.315 in. (8 mm)	25845	1.5 PSF
38 Series Cedar Texture Panel No Groove Shiplap Edge (strand)	8 ft. (96 in.)(2.4 m)	No Groove	N/A	48.56 in. (123.4 cm)	0.315 in. (8 mm)	25855 *	1.5 PSF
	9 ft. (108 in.)(2.7 m)	No Groove	N/A	48.56 in. (123.4 cm)	0.315 in. (8 mm)	29189 *	1.5 PSF
	10 ft. (120 in.)(3.0 m)	No Groove	N/A	48.56 in. (123.4 cm)	0.315 in. (8 mm)	25825 *	1.5 PSF
38 Series Cedar Texture Panel No Groove Square Edge (strand)	8 ft. (96 in.)(2.4 m)	No Groove	N/A	48.56 in. (123.4 cm)	0.315 in. (8 mm)	41044	1.5 PSF
76 Series Cedar Texture Panel 4" and 8" o.c. (strand)	8 ft. (96 in.)(2.4 m)	4 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25831	1.5 PSF
	9 ft. (108 in.)(2.7 m)	4 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25832 *	1.5 PSF
	10 ft. (120 in.)(3.0 m)	4 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25833 *	1.5 PSF
	8 ft. (96 in.)(2.4 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25848	1.5 PSF
	9 ft. (108 in.)(2.7 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25850	1.5 PSF
	10 ft. (120 in.)(3.0 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25851	1.5 PSF
76 Series Cedar Texture Panel No Groove Shiplap Edge (strand)	8 ft. (96 in.)(2.4 m)	No Groove	N/A	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25856	1.5 PSF
	9 ft. (108 in.)(2.7 m)	No Groove	N/A	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25857	1.5 PSF
	10 ft. (120 in.)(3.0 m)	No Groove	N/A	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25858	1.5 PSF
190 Series Cedar Texture 8" o.c. (strand)	8 ft. (96 in.)(2.4 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.530 in. (14 mm)	25852	2 PSF
	9 ft. (108 in.)(2.7 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.530 in. (14 mm)	25853 *	2 PSF
	10 ft. (120 in.)(3.0 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.530 in. (14 mm)	25854 *	2 PSF
190 Series Cedar Texture Panel No Groove Shiplap Edge (strand)	8 ft. (96 in.)(2.4 m)	No Groove	N/A	48.56 in. (123.4 cm)	0.530 in. (14 mm)	25859 *	2 PSF
	9 ft. (108 in.)(2.7 m)	No Groove	N/A	48.56 in. (123.4 cm)	0.530 in. (14 mm)	25860 *	2 PSF
	10 ft. (120 in.)(3.0 m)	No Groove	N/A	48.56 in. (123.4 cm)	0.530 in. (14 mm)	25861 *	2 PSF
76 Series Cedar Texture Siding Panel and Soffit 8" o.c. (fiber)	8 ft. (96 in.)(2.4 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25934	2 PSF
	9 ft. (108 in.)(2.7 m)	8 in. o.c.	3/8 in. (10 mm)	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25935	2 PSF
76 Series Cedar Texture Siding Panel and Soffit - Square Edge (fiber)	8 ft. (96 in.)(2.4 m)	No Groove	N/A	47.94 in. (121.8 cm)	0.375 in. (10 mm)	25926	2 PSF
	9 ft. (108 in.)(2.7 m)	No Groove	N/A	47.94 in. (121.8 cm)	0.375 in. (10 mm)	25927	2 PSF

STUCCO TEXTURE PANEL


THE RICH LOOK OF STUCCO MADE EASIER

- The remarkably detailed soft, earthy, hand-troweled effect of stucco on a panel
- Deeply textured and varied from board to board
- Comes in easy-to-install shiplap edge panels
- Available pre-primed
- Not rated for structural use
- Treated engineered wood fiber substrate



Stucco texture

STUCCO TEXTURE PANEL (FIBER)



DESCRIPTION	LENGTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
Stucco Texture Panel (fiber)	8 ft. (96 in.)(2.4 m)	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25912	2 PSF
	9 ft. (108 in.)(2.7 m)	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25913	2 PSF


SMOOTH FINISH PANEL (FIBER)

DESIGNED FOR EASE AND PERFORMANCE

- The shiplap edge makes it easier to install
- Pre-primed for exceptional paint adhesion
- Not rated for structural use
- Smooth finish
- Treated engineered wood fiber substrate

Smooth Finish

76 SERIES SMOOTH FINISH PANEL 8"O.C. (FIBER)



76 SERIES SMOOTH FINISH SIDING PANEL AND SOFFIT - SQUARE EDGE (FIBER)



GROOVE DETAIL




DESCRIPTION	LENGTH	GROOVE	GROOVE WIDTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
76 Series Smooth Finish Panel 8" o.c. (fiber)	8 ft. (96 in.)(2.4 m)	8 in. o.c.	1/4 in. (6 mm)	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25932	2 PSF
76 Series Smooth Finish Panel 8" o.c. (fiber) with slip sheets	8 ft. (96 in.)(2.4 m)	8 in. o.c.	1/4 in. (6 mm)	48.56 in. (123.4 cm)	0.375 in. (10 mm)	39051	2 PSF
76 Series Smooth Finish Siding Panel and Soffit - Square Edge (fiber)	8 ft. (96 in.)(2.4 m)	No Groove	N/A	47.94 in. (121.8 cm)	0.375 in. (10 mm)	25930	2 PSF
	9 ft. (108 in.)(2.7 m)	No Groove	N/A	47.94 in. (121.8 cm)	0.375 in. (10 mm)	25931	2 PSF

REVERSE BOARD & BATTEN

THE RESILIENT SPIRIT OF HISTORIC ARCHITECTURE

- Rustic and cross-sawn texture, this panel features the weathered grain appearance of cedar
- Available in 8' and 9' lengths
- Shiplap edges make it easier to level and apply
- Pre-primed for exceptional paint adhesion
- Not rated for structural use
- Treated engineered wood fiber substrate

REVERSE BOARD AND BATTEN CEDAR TEXTURE 12" PANEL O.C. (FIBER)



DESCRIPTION	LENGTH	GROOVE	GROOVE WIDTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
Reverse Board and Batten Cedar Texture Panel 12" o.c. (fiber)	8 ft. (96 in.)(2.4 m)	12 in. o.c.	1 in. (2.5 cm)	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25915	2 PSF
	9 ft. (108 in.)(2.7 m)	12 in. o.c.	1 in. (2.5 cm)	48.56 in. (123.4 cm)	0.375 in. (10 mm)	25917	2 PSF



Specifications: LP® SmartSide® Vertical Siding


VERTICAL SIDING

CHARMING STYLE FOR AMERICAN HOMES

- Re-creates the stylish appearance of board & batten
- 16' lengths eliminate horizontal joints
- Coordinates with LP SmartSide Trim
- Pre-primed for exceptional paint adhesion
- Not rated for structural use
- Treated engineered wood strand substrate



VERTICAL SIDING



DESCRIPTION	LENGTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
38 Series Cedar Texture Vertical	16 ft. (192 in.)(4.9 m)	15.94 in. (40.5 cm)	0.315 in. (8 mm)	40503	1.5 PSF
Siding - No Groove (strand)					

Specifications: LP® SmartSide® Trim

CEDAR TEXTURE TRIM

THE CLASSIC APPEARANCE OF CEDAR

- Interior or exterior use, including corner boards, windows and doors
- Narrow widths save cutting time
- Pre-primed for exceptional paint adhesion
- 16' length can result in faster installation and fewer seams
- Treated engineered wood strand substrate

190 SERIES CEDAR TEXTURE TRIM (STRAND)



440 SERIES CEDAR TEXTURE TRIM (STRAND)




540 SERIES CEDAR TEXTURE TRIM (STRAND)



$(3.8\ cm,\,6.4\ cm,\,8.9\ cm,\,11.4\ cm,\,14.0\ cm,\,18.3\ cm,\,23.4\ cm\ or\ 28.5\ cm)$

440 SERIES CEDAR TEXTURE PLOUGHED FASCIA (STRAND)



DESCRIPTION	LENGTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
190 Series Cedar Texture Trim (strand)	16 ft. (192 in.)(4.9 m)	2.50 in. (6.4 cm)	0.530 in. (14 mm)	28448	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (8.9 cm)	0.530 in. (14 mm)	28450	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (14.0 cm)	0.530 in. (14 mm)	28452	2 PSF
440 Series Cedar Texture Trim (strand)	16 ft. (192 in.)(4.9 m)	1.50 in. (3.8 cm)	0.625 in. (16 mm)	25877	2 PSF
	16 ft. (192 in.)(4.9 m)	2.50 in. (6.4 cm)	0.625 in. (16 mm)	25878	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (8.9 cm)	0.625 in. (16 mm)	25880	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (14.0 cm)	0.625 in. (16 mm)	25882	2 PSF
	16 ft. (192 in.)(4.9 m)	7.21 in. (18.3 cm)	0.625 in. (16 mm)	25883	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (23.4 cm)	0.625 in. (16 mm)	25884	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (28.5 cm)	0.625 in. (16 mm)	25885	2 PSF
540 Series Cedar Texture Trim (strand)	16 ft. (192 in.)(4.9 m)	1.50 in. (3.8 cm)	0.910 in.(23 mm)	25886 *	3 PSF
	16 ft. (192 in.)(4.9 m)	2.50 in. (6.4 cm)	0.910 in.(23 mm)	25887 *	3 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (8.9 cm)	0.910 in.(23 mm)	25888	3 PSF
	16 ft. (192 in.)(4.9 m)	4.50 in. (11.4 cm)	0.910 in.(23 mm)	25889 *	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (14.0 cm)	0.910 in.(23 mm)	25890	3 PSF
	16 ft. (192 in.)(4.9 m)	7.21 in. (18.3 cm)	0.910 in.(23 mm)	25891	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (23.4 cm)	0.910 in.(23 mm)	25892	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (28.5 cm)	0.910 in.(23 mm)	25893	3 PSF
440 Series Cedar Texture Ploughed Fascia (strand)	16 ft. (192 in.)(4.9 m)	5.50 in. (14.0 cm)	0.625 in. (16 mm)	27240 *	2 PSF
	16 ft. (192 in.)(4.9 m)	7.21 in. (18.3 cm)	0.625 in. (16 mm)	27819 *	2 PSF

Specifications: LP® SmartSide® Trim

REVERSIBLE TRIM (FIBER)

TWO GREAT LOOKS IN ONE

- The natural look of cedar texture on one side and smooth finish on the other
- Interior or exterior use, including corner boards, windows and doors
- Pre-primed for exceptional paint adhesion
- 16' length can result in faster installation and fewer seams
- Reversible trim has a 1/8" bevel cut on its cedar texture side and is square cut on the smooth finish side
- Treated engineered wood fiber substrate

440 SERIES REVERSIBLE TRIM (FIBER)



540 SERIES REVERSIBLE TRIM (FIBER)







Cedar Texture



Smooth Finish

DESCRIPTION	LENGTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
440 Series Reversible Trim (fiber)	16 ft. (192 in.)(4.9 m)	2.70 in. (6.9 cm)	0.625 in. (16 mm)	25940	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (8.9 cm)	0.625 in. (16 mm)	25941	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (14.0 cm)	0.625 in. (16 mm)	25942	2 PSF
	16 ft. (192 in.)(4.9 m)	7.21 in. (18.3 cm)	0.625 in. (16 mm)	25943	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (23.4 cm)	0.625 in. (16 mm)	25944	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (28.5 cm)	0.625 in. (16 mm)	25945	2 PSF
	16 ft. (192 in.)(4.9 m)	15.47 in. (39.3 cm)	0.625 in. (16 mm)	38445	2 PSF
540 Series Reversible Trim (fiber)	16 ft. (192 in.)(4.9 m)	3.50 in. (8.9 cm)	0.910 in. (23 mm)	25946	3 PSF
	16 ft. (192 in.)(4.9 m)	4.50 in. (11.4 cm)	0.910 in. (23 mm)	25947	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (14.0 cm)	0.910 in. (23 mm)	25948	3 PSF
	16 ft. (192 in.)(4.9 m)	7.21 in. (18.3 cm)	0.910 in. (23 mm)	25949	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (23.4 cm)	0.910 in. (23 mm)	25950	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (28.5 cm)	0.910 in. (23 mm)	25951	3 PSF

SMOOTH FINISH TRIM (STRAND)

SMOOTH APPEARANCE, ADVANCED DURABILITY OF ENGINEERED WOOD

- Advanced Durability for Longer Lasting BeautyTM
- Holds up in extreme weather including moisture, hail, freeze/thaw cycles, and up to 200 mph wind gusts
- Treated with the SmartGuard® process for superior protection against the weather, fungal decay and termites
- 16' ft length can result in faster installation and fewer seams
- Pre-primed for exceptional paint adhesion
- Backed by an industry-leading 5/50-year limited warranty
- Treated engineered wood strand substrate





Smooth Finish





DESCRIPTION	LENGTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
440 Series Smooth Finish Trim (strand)	16 ft. (192 in.)(4.9 m)	1.50 in. (3.8 cm)	0.625 in. (16 mm)	41640	2 PSF
	16 ft (192 in.) (4.9 m)	2.50 in. (6.4 cm)	0.625 in. (16 mm)	41627	2 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (8.9 cm)	0.625 in. (16 mm)	41420	2 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (14.0 cm)	0.625 in. (16 mm)	41422	2 PSF
	16 ft. (192 in.)(4.9 m)	7.21 in. (18.3 cm)	0.625 in. (16 mm)	41423	2 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (23.4 cm)	0.625 in. (16 mm)	41492	2 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (28.5 cm)	0.625 in. (16 mm)	41490	2 PSF
540 Series Smooth Finish Trim (strand)	16 ft. (192 in.)(4.9 m)	1.50 in. (3.8 cm)	0.910 in. (23 mm)	41629	3 PSF
	16 ft. (192 in.)(4.9 m)	2.50 in. (6.4 cm)	0.910 in. (23 mm)	41628	3 PSF
	16 ft. (192 in.)(4.9 m)	3.50 in. (8.9 cm)	0.910 in. (23 mm)	41342	3 PSF
	16 ft. (192 in.)(4.9 m)	5.50 in. (14.0 cm)	0.910 in. (23 mm)	41343	3 PSF
	16 ft. (192 in.)(4.9 m)	7.21 in. (18.3 cm)	0.910 in. (23 mm)	41344	3 PSF
	16 ft. (192 in.)(4.9 m)	9.21 in. (23.4 cm)	0.910 in. (23 mm)	41345	3 PSF
	16 ft. (192 in.)(4.9 m)	11.21 in. (28.5 cm)	0.910 in. (23 mm)	41494	3 PSF

Specifications: LP® SmartSide® Soffit

CEDAR TEXTURE SOFFIT

THE FINISHING TOUCH

- The perfect alternative to MDO and plywood soffits
- Cut-to-width eliminates time spent ripping full sheets
- 38 Series engineered for closed soffit applications
- The 76 Series and 190 Series are ideal for use as the starter course for roofs with exposed eaves
- Treated engineered wood strand substrate

ALSO AVAILABLE IN FIBER SUBSTRATE.

- Not rated for exposed eave applications
- Engineered for closed soffit applications
- Treated engineered wood fiber substrate





Cedar Texture

38 SERIES 4' x 8' CEDAR TEXTURE SOFFIT (STRAND)



76 SERIES 4'x 8' CEDAR TEXTURE SOFFIT (STRAND)



190 SERIES 4'x 8' CEDAR TEXTURE SOFFIT (STRAND)



38 SERIES CEDAR TEXTURE SOFFIT – CUT-TO-WIDTH (STRAND)



76 SERIES CEDAR TEXTURE SOFFIT – CUT-TO-WIDTH (STRAND)



76 SERIES CEDAR TEXTURE SOFFIT (FIBER)



DESCRIPTION	LENGTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
38 Series 4' x 8' Cedar Texture Soffit (strand)	8 ft. (96 in.)(2.4 m)	47.88 in. (121.6 cm)	0.315 in. (8 mm)	25813	-
76 Series 4' x 8' Cedar Texture Soffit (strand)	8 ft. (96 in.)(2.4 m)	47.88 in. (121.6 cm)	0.375 in. (10 mm)	25814	-
190 Series 4' x 8' Cedar Texture Soffit (strand)	8 ft. (96 in.)(2.4 m)	47.88 in. (121.6 cm)	0.530 in. (14 mm)	25816 *	-
38 Series Cedar Texture Soffit – Cut-to-Width (strand)	16 ft. (192 in.)(4.9 m)	11.94 in. (30.3 cm)	0.315 in. (8 mm)	25805	-
	16 ft. (192 in.)(4.9 m)	15.94 in. (40.5 cm)	0.315 in. (8 mm)	25806	-
	16 ft. (192 in.)(4.9 m)	23.94 in. (60.8 cm)	0.315 in. (8 mm)	25807	-
76 Series Cedar Texture Soffit – Cut-to-Width (strand)	16 ft. (192 in.)(4.9 m)	11.94 in. (30.3 cm)	0.375 in. (10 mm)	25808	-
76 Series Cedar Texture Soffit and Siding Panel (fiber)	8 ft. (96 in.)(2.4 m)	47.94 in. (121.8 cm)	0.375 in. (10 mm)	25926	2 PSF
	9 ft. (108 in.)(2.7 m)	47.94 in. (121.8 cm)	0.375 in. (10 mm)	25927	2 PSF
76 Series Cedar Texture Soffit – Cut-to-Width (fiber)	16 ft. (192 in.)(4.9 m)	15.94 in. (40.5 cm)	0.375 in. (10 mm)	28756	-

Specifications: LP® SmartSide® Soffit

VENTED SOFFIT


ENGINEERED TO CUT OUT PROBLEMS


- The perfect alternative to MDO, plywood or hand-installed metal vents
- Precisely cut vents offer 10 square inches of ventilation per linear foot, making it easier to meet code requirements while adding architectural beauty
- Designed to minimize paint buildup and promote continuous airflow
- 1/8" vents to help keep hornets and bees out
- Eliminates time spent ripping full sheets
- Treated engineered wood strand substrate



Cedar Texture

38 SERIES VENTED CEDAR TEXTURE SOFFIT - CUT-TO-WIDTH (STRAND)





DESCRIPTION	LENGTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
38 Series Vented Cedar Texture Soffit – Cut-to-Width (strand)	16 ft. (192 in.)(4.9 m)	11.94 in. (30.3 cm)	0.315 in. (8 mm)	25822	-
	16 ft. (192 in.)(4.9 m)	15.94 in. (40.5 cm)	0.315 in. (8 mm)	25823	-
	16 ft. (192 in.)(4.9 m)	23.94 in. (60.8 cm)	0.315 in. (8 mm)	25824	-

Specifications: LP® SmartSide® Soffit

SMOOTH FINISH SOFFIT (FIBER)

THE PERFECT MATCH

- Installs quickly and easily
- Pre-primed for exceptional paint adhesion
- Smooth finish
- Treated engineered wood fiber substrate

76 SERIES SMOOTH FINISH SOFFIT (FIBER)







DESCRIPTION	LENGTH	ACTUAL WIDTH	MINIMUM THICKNESS	PID NUMBER	WEIGHT
76 Series Smooth Finish Soffit and Siding Panel (fiber)	8 ft. (96 in.)(2.4 m)	47.94 in. (121.8 cm)	0.375 in. (10 mm)	25930	2 PSF
	9 ft. (108 in.)(2.7 m)	47.94 in. (121.8 cm)	0.375 in. (10 mm)	25931	2 PSF
76 Series Smooth Finish Soffit and Siding Panel (fiber) with slip sheet	8 ft. (96 in.)(2.4 m)	47.94 in. (121.8 cm)	0.375 in. (10 mm)	39052	2 PSF
	9 ft. (108 in.)(2.7 m)	47.94 in. (121.8 cm)	0.375 in. (10 mm)	39050	2 PSF

START STRONG WITH LP BUILDING SOLUTIONS

Inventing a Better Tomorrow with LP

LP's mission is to engineer extraordinary solutions for everyday problems. With a united spirit of discovery, LP is forging ahead with innovative ideas to create new products that offer exceptional performance for today's building challenges.

LP® ArmorStrand® Panel Substrate Under Textured Finish Coatings

LP ArmorStrand substrate is engineered to deliver a strong foundation to help create the look of stucco with durable acrylic finishes. It's toughness you can build on with confidence.

LP® FlameBlock® Fire-Rated Sheathing

LP FlameBlock Fire-Rated Sheathing has structural design values equal to standard sheathing in the same performance category. ICC-certified (ESR-1365) per AC264 with a Class A and 30-minute Flame Spread Rating (ASTM E84), it combines fire resistance and impressive structural performance in a single panel.

LP® TechShield® Radiant Barrier

The original, #1 brand of radiant barrier, LP TechShield Radiant Barrier may reduce monthly cooling costs by blocking up to 97% of the radiant heat in the panel from emitting into a home's attic, lowering attic temperatures by up to 30° F.

LP Legacy® Premium Sub-Flooring

LP Legacy sub-flooring uses Gorilla Glue Technology® for one of the strongest, stiffest sub-floors. The resin in Gorilla Glue Technology binds wood fibers at the molecular level for premium performance.



For more information, visit LPSmartSide.com

MARNING: Drilling, sawing, sanding or machining wood products can expose you to wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information go to www.P65Warnings.ca.gov/wood.